


## Modellblatt



**Farbe**

- 93 White  
test ral
- 18 Graphit  
ADAPTA RF 9913 WX
- 58 Creme  
RAL 7044

**LED-Temperaturfarbe** 2700 K / 3500 K / 4000 K

**Dimmen** CASAMBI / DALI 1-10V Push

**Installationstyp** Surface Canopy

**Materialien** Schirm: Eichenholz

**Lichtquelle** 1 x LED PLATE 26W 500mA



**LED** CRI>90 2206 lm 98  
2700 K / 3500 K / 4000 K

**Driver** Constant Current 500 110~240 V V 50~60 Hz HZ



**Anwendung** Deckenleuchten

**Verpackung** 1 Kartons  
0.593 m x 0.785 m x 0.785 m  
Bruttogewicht 20.3  
Nettogewicht 14  
Vol. 0.3654

### Lichteffect

#### Allgemeinbeleuchtung

Beleuchtungskörper für die allgemeine Beleuchtung, der das Licht gleichmäßig in alle Richtungen verteilt.



### Photometrische Daten

**Effizienz** 49.81 lm/W  
**Koordinatensystem** CG  
**Gesamtfluss** 1284.41 lm  
**Höchster Wert** 727.04 cd

### Andere Anwendungen

