




# Florian Schulz

## One 58

### Version

- brass burnished lacquered
- brass dark burnished lacquered
- brass matt brushed lacquered
- brass polished lacquered
- brass polished unlacquered
- chrome-plated brass
- copper-plated brass lacquered
- copper-plated brass matt brushed lacquered
- nickel-plated brass
- brass nickel-plated lacquered
- brass nickel-plated matt brushed

### Technical details

|                             |   |
|-----------------------------|---|
| Country of Manufacture      |  Germany |
| Manufacturer                | Florian Schulz  |
| Designer                    | Jens Schump   |
| Year of design              | 2019  |
| protection                  | IP20  |
| Scope of delivery           | LED   |
| Diameter in cm              | 58  |
| material                    | brass   |
| height adjustment           | height determinable   |
| dimming                     | on site dimmable with a trailing edge dimmer  |
| Wattage                     | 31.4 W  |
| LED                         | inclusive   |
| Colour Rendering Index      | >95   |
| Luminous flux in lm         | 3,020   |
| Color temperature in Kelvin | 2,700 extra warm white  |
| canopy dimensions           | 25 cm   |
| light distribution          | directly and indirectly   |
| total height                | 100 - 200 cm  |
| Dimensions                  | H 2 cm   Ø 58 cm  |

### Description

The VS Manufaktur One 58 pendant lamp has a diameter of 58 cm and a height of 2 cm. The ring-shaped lamp radiates light simultaneously upwards and downwards. The total height is a maximum of 200 cm and can be set to a minimum of 100 cm. This lamp is also available with other suspension heights on request. The One 58 is available in these finishes: Brass chrome-plated, polished lacquered, nickel-plated, nickel-plated matt brushed, burnished lacquered, dark burnished lacquered, copper-plated, nickel-plated lacquered, polished unlacquered, brass copper-plated matt brushed lacquered and matt brushed lacquered. An LED with a diffuser is integrated as a light source so that the light is always glare-free. Only the 230-240 volt pendant lamp can be dimmed on site. The 110 - 125 volt version is supplied here as a non-dimmable version.