


Mawa

Wittenberg 4.0 Parquet floor lamp LED

Oberfläche

- black
- beige
- blue
- grey
- red
- white

Technical details

Country of Manufacture	 Germany
Manufacturer	Mawa
Designer	Jan Dinnebier
Designer 2	mawa engineering
protection	IP20
Scope of delivery	LED
material	aluminum, metal
beam angle	38 degrees
cable color	black
cable length	250 cm
dimming	integrated Pushbutton dimmer
switchability	Foot switch
LED	inclusive
Colour Rendering Index	95
Color temperature in Kelvin	2,700 extra warm white
light head dimensions	8 cm
bulb exchange	on site itself
system performance	2 x 12,7 Watt
Total luminous flux in lm	2,200
light distribution	directly
Dimensions	H 13 cm B 10 cm L 20 cm

Description

The Mawa Wittenberg 4.0 Parquet floor lamp LED has two half-flush integrated spotlight heads. The lamp heads are individually adjustable, each lamp head can be swivelled by 90 degrees and rotated by 365 degrees. The light is switched on and off via a foot switch on the supply line. The two lamp heads can be dimmed separately and continuously via two push-button dimmers on the lamp. A memory function saves the last selected luminous intensity of the two lamp heads and automatically re-adjusts it when switched on again.

The Wittenberg 4.0 Parquet Floor Lamp LED is available with powder-coated black matt, beige, grey, blue, red or white matt surfaces. On request, this lamp is also offered with a black housing and lamp heads in copper, brass or chrome. As standard, the integrated LEDs have a colour temperature of 2,700 Kelvin extra warm white. On request they are also on offer with 3,000 Kelvin warm white or 4,000 Kelvin white. The colour rendering index of the lamp is Ra 92. On request it is also available with Ra 98, which is closer to natural light (Ra 100). The cable outlet can be selected on the longer or shorter side of the housing. The scope of delivery includes a honeycomb grid with which the light can be emitted without glare.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.