

# Bover

## Amphora 02 LED



### Oberfläche

- beige
- brown

### Dimmbarkeit

- on site dimmable with a trailing edge dimmer
- not dimmable

## Technical details

|                                     |   |
|-------------------------------------|---|
| <b>Country of Manufacture</b>       |  Spain |
| <b>Manufacturer</b>                 | Bover   |
| <b>Designer</b>                     | Alex Fernandez Camps  |
| <b>Designer 2</b>                   | Gonzalo Mila  |
| <b>Year of design</b>               | 2013  |
| <b>Protection class / IP rating</b> | IP66  |
| <b>Contents of the package</b>      | LED   |
| <b>Diameter in cm</b>               | 80  |
| <b>material</b>                     | aluminum, polyethylene, stainless Steel   |
| <b>cable color</b>                  | black   |
| <b>cable length</b>                 | 369 cm  |
| <b>Wattage</b>                      | 24.7 W  |
| <b>LED</b>                          | inclusive   |
| <b>Colour Rendering Index</b>       | 90  |
| <b>Luminous flux in lm</b>          | 3,000   |
| <b>Color temperature in Kelvin</b>  | 2,700 extra warm white  |
| <b>bulb exchange</b>                | at the manufacturer / at the factory  |
| <b>Dimensions</b>                   | H 123 cm   Ø 80 cm  |

## Description

The bellied lamp body of the Bover Amphora 02 LED is woven by hand and consists of polyethylene. The floor lamp is available in the surfaces light beige and brown. The light shines through the woven lamp body in rattan look. The three-legged lamp base of the Amphora 02 LED by Bover is provided with a brown oxidation protection.

The Amphora 02 LED has a power-efficient LED with a colour temperature of 2,700 Kelvin extra warm white. This floor lamp, which is also suitable for outdoor use, is available as non-dimmable or dimmable with a trailing edge phase dimmer. The non-dimmable floor lamp is connected via a 369 cm long black cable with plug. The dimmable lamp is connected via a connection box and can be fixed to the floor using the accessories supplied. The lamp can be fixed to concrete, hollow concrete, lightweight concrete, brick, hollow brick and natural stone.