

# Byok


## Piani Quadro 48 Downlight



### Oberfläche

- Aluminio pulido
- aluminio mate
- negro mate

### Technical details

<b>País de origen</b>	 Alemania
<b>Fabricante</b>	Byok
<b>Diseñador</b>	Kai Byok
<b>Índice de protección / Protección IP</b>	IP20
<b>Contenido del paquete</b>	LED
<b>material</b>	aluminio
<b>longitud del cable</b>	250 cm
<b>Ajuste de altura</b>	altura determinada
<b>Atenuación</b>	Regulable en el sitio con control de fase inversa
<b>LED</b>	incluyendo
<b>LED (reemplazable)</b>	sí
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>El rendimiento del sistema</b>	8 x 3,6 Watt
<b>Flujo total luminoso en lm</b>	2.450
<b>distribución de la luz</b>	directamente
<b>Dimensions</b>	H 0,8 cm   B 48 cm   L 48 cm

### Descripción

The Byok Piani Quadro 48 Downlight is a pendant lamp. The strip geometry being 8 mm thin is milled out of massive aluminium and polished by hand afterwards. The reflective surface is only broken by four fine ropes out of copper braid providing for the power supply. The canopy has a diameter of 26 cm and a height of 6.8 cm. The Piani Quadro 48 Downlight runs by eight LEDs being dazzle-free installed due to the reflector technics used and which may be exchanged singly.

The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.