

Byok

Grado L 2




Oberfläche

- aluminio mate
- negro mate
- blanco mate

Dimmbarkeit

- DALI regulable
- Luz natural y sensor de movimiento
- Luz natural y sensor de movimiento con sensor para luz superior

Technical details

País de origen	 Alemania
Fabricante	Byok
Diseñador	Kai Byok
Índice de protección / Protección IP	IP20
Contenido del paquete	LED
Proyección en cm	151
material	aluminio
longitud del cable	300 cm
Potencia en vatios	87 W
Indice de reproduccion cromatica	80
Temperatura de color en grados Kelvin	3.000 blanco cálido
Dimensiones del soporte de la lámpara	50 x 35 cm
Flujo total luminoso en lm	14.000
distribución de la luz	directa e indirectamente
Dimensions	H 204 cm

Descripción

The Byok Grado L 2 floor lamp emits light both downwards and upwards. This lamp has a 151 cm long lamp arm and can be attached directly to the furniture or positioned movably with one base. It is available in three versions: DALI dimmable or with an integrated daylight and motion sensor with and without an additional uplight sensor.

The Grado L 2 is particularly suitable for lighting two workstations. In the two versions with daylight and motion sensors, each workstation is assigned to a single sensor, so that two workstations can be illuminated differently. The floor lamp is offered in matt anodised aluminum, matt black and matt white. It is supplied with a colour temperature of 3,000 Kelvin warm white, on request it is also available with a colour temperature of 4,000 Kelvin white.