



LDM

Kyno Spot Uno Surface-mounted Round

Oberfläche

- aluminio mate
- aluminio pulido
- negro
- bronce
- blanco

Elemente

- cromo
- negro
- oro
- aluminio pulido
- blanco

Dimmbarkeit

- DALI regulable
- Regulable en el sitio con control de fase inversa
- con módulo Casambi

Technical details

País de la Fabricación	 Alemania
fabricante	LDM
protección	IP20
Volumen de suministro	LED
material	aluminio
angulo del rayo	20 - 60 grados
Potencia en vatios	12 W
LED	incluyendo
Indice de reproduccion cromatica	97
El flujo luminoso en lm	1.252
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
Dimensiones del dosel	10 cm
cabeza del alumbrado masa	Longitud 18 cm, 4 cm en el fabricante / en la fabrica
reemplazo de la bombilla:	

Descripción

The LDM Kyno Spot Uno Surface-mounted Round is a surface-mounted ceiling spot made of aluminum. The light is focused by a frosted, optical glass lens. The beam angle of the light can be continuously adjusted between 20 and 60 degrees by turning the glass lens out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Kyno Spot Uno Surface-mounted Round is available in the surfaces aluminum polished, aluminum matt, bronze, white and black matt. The ring-shaped design element on the lamp head is available in aluminum polished, matt chrome-plated, matt gold-plated, white matt and black matt. The swivel joint has the same surface as the design element, only the lamp with the element in aluminum polished has a chrome-plated swivel joint. The lamp head is a total of 18 cm long without unscrewing the lens and has a diameter of 4 cm.

The Kyno surface-mounted ceiling spotlight is offered with three dimming options: on site dimmable with a trailing edge phase dimmer, DALI dimmable or with an integrated Casambi module. The Kyno Spot Uno Surface-mounted Round is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request, the spotlight is also available with 3,000 Kelvin warm white, 4,000 Kelvin white or with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,000 Kelvin warm white to 1,800 Kelvin extra warm white). The lamp is operated with Full Spectrum LEDs whose light resembles sunlight.