


Pendelleuchte | 220-240 V | 1x2GX13
6860



| Technische Daten | |
|---|---------------------|
| Installationsposition | Decke |
| Installationsumgebung | Indoor |
| Lampenleistung | 1 x 55 W |
| Anschluss der Leuchte | 1 x 2GX13 |
| Optik | General Lighting |
| Light emission direction | downward and upward |
| Isolierklasse | 1 |
| IP | IP20 |
| IP optisches System | IP40 |
| Glühdrahtprüfung | 650° |
| Direkte Montage auf normal entflammaren Oberflächen | Ja |
| CE | Ja |
| ETL | Nein |
| Fire Rated (BS 476 PT21 compliant) | Nein |
| Einschließlich Driver | Driver |
| Induction | Nein |
| Notbeleuchtung | Nein |
| Schwenkbarkeit | Nein |
| Drehbarkeit | Nein |
| Begehrbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Nein |
| Harzbeschichtung | Nein |
| Typ Lichtabstrahlung | Zweiflammig |
| Nettogewicht | 6.000 Kg |

| Oberfläche Diffusor | |
|---------------------|---------|
| Material | PE |
| Farbe | neutral |

Pendelleuchte | 220-240 V | 1x2GX13
6860

Double emission pendant luminaires for indoor application. Fluorescent lamp included 55W, lamp cap 1x2GX13.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 6.000 kg.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Eigenschaften | |
|---------------------------------|---------|
| Light Output Ratio (LOR) | 88 % |
| Lichtstrom (Lichtquelle) | 4200 lm |
| Leuchten Lichtstrom | 3700 lm |
| Consumption | 59 W |
| Leuchten Lichtausbeute | 71 lm/W |
| Farbtemperatur | 3000 K |
| Farbwiedergabeindex | 80 Ra |

| UGR | |
|-------------------|----------|
| X=4H Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |
| UGR transversal | < 16 |
| UGR axial | < 16 |

| OPTICAL | |
|-----------------------------|---------------|
| Light distribution simmetry | Symmetrical 2 |
| Ottica C0/C180 | 122° |
| Ottica C90/C270 | 116° |

