




Mawa

Wittenberg 4.0 ceiling lamp 2-lights LED

Oberfläche

- chrome
- noir
- blanc

Technical details

| | |
|--|---|
| Pays de fabrication |  Allemagne |
| Fabricant | Mawa |
| Créateur | Jan Dinnebier |
| Créateur 2 | mawa engineering |
| Indice de protection / Indice IP | IP20 |
| Contenu de la livraison matériel | LED aluminium, métal |
| angle du faisceau | 38 degrees |
| atténuation | gradable avec variateur à coupure de phase et à commande de phase |
| LED | y compris |
| Indice de rendu des couleurs | 95 |
| La température de couleur en Kelvin | 2.700 extra blanc chaud |
| tête de luminaire masse | 8 cm |
| remplacement des ampoules : | sur le site meme |
| Les performances du système | 2 x 12,7 Watt |
| Flux lumineux total en LM | 2.200 |
| répartition de la lumière | directement |
| Dimensions | H 9 cm B 8 cm L 18 cm |

Description

The Mawa Wittenberg 4.0 ceiling lamp 2-lights LED has two spotlight lamp heads, which are independently adjustable. Each lamp head can be swivelled 90 degrees and rotated 365 degrees. The light emission surface of this lamp is particularly large and well glare-free. With this compact, rectangular lamp design, neither screws nor cables are visible. The Wittenberg 4.0 ceiling lamp 2-lights LED is available in powder-coated white matt or black matt surfaces.

The integrated LEDs each have a colour temperature of 2,700 Kelvin extra warm white and can be dimmed on site with a leading or trailing edge phase dimmer. On request they are also available with 3,000 Kelvin warm white or 4,000 Kelvin white. In addition, the lamp is also on request on offer as DALI, Bluetooth or 1-10 volt dimmable versions. The Wittenberg 4.0 ceiling lamp 2-lights LED is also on request available with a colour rendering index of Ra 98, which is closer to natural light (Ra 100).

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.