




Mawa

Wittenberg 4.0 ceiling lamp Downlight LED

Oberfläche

- noir
- blanc

Technical details

Pays de fabrication	 Allemagne
Fabricant	Mawa
Créateur	Jan Dinnebier
Créateur 2	mawa engineering
Indice de protection / Indice IP	IP20
Contenu de la livraison	LED
Diamètre en cm	8
matériel	aluminium, métal
angle du faisceau	38 degrees
atténuation	gradable avec variateur à coupure de phase et à commande de phase
Puissance en Watt	12,7 W
LED	y compris
Indice de rendu des couleurs	95
Flux lumineux en lm	1.100
La température de couleur en Kelvin	2.700 extra blanc chaud
remplacement des ampoules :	sur le site meme
répartition de la lumière	directement
Dimensions	H 12 cm Ø 8 cm

Description

The Mawa Wittenberg 4.0 ceiling lamp Downlight LED emits its light directly and bundled downwards. Neither screws nor cables are visible in the compact design of the lamp. This lamp has a height of 11.5 cm and a diameter of 7.6 cm. An LED is integrated as a light source, which can be dimmed by the customer with a leading or trailing edge phase dimmer. On request, the lamp is also available as a DALI or 1-10 volt dimmable version. These two optionally available versions (DALI or 1-10 Volt) then have a height of 14.7 cm with a diameter of 7.6 cm. The Wittenberg 4.0 ceiling lamp Downlight LED is available with powder-coated black matt or white matt surfaces. The integrated LED has a colour temperature of 2,700 Kelvin extra warm white. On request it is also offered with 3,000 Kelvin warm white or 4,000 Kelvin white.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.