




Mawa

Bullauge 6 pendant mounting

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

Pays de fabrication	 Allemagne
fabricant	Mawa
concepteur	Martin Wallroth
surface	weiß matt / white matt
protection	IP20
Contenu de la livraison	LED
matériel	verre acrylique, aluminium
longueur de câble	250 cm
réglage de la hauteur	hauteur déterminée
atténuation	gradable avec variateur à coupure de phase et à commande de phase
LED	y compris
Indice de rendu des couleurs	>90
répartition de la lumière	directement
Dimensions	H 10 cm

Description

The Mawa Bullauge 6 pendant mounting emits its light directly downwards. This pendant lamp is offered with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. The lamp is supplied as standard in powder-coated white matt aluminum. The even distribution of the LEDs and the opaque, satin diffuser made of plexiglass creates a diffuse and very homogeneous lighting surface. The Bullauge 6 pendant mounting is suspended for the three smaller versions on three parallel cables with a maximum length of 250 cm, the largest lamp with a diameter of 120 cm is suspended on four parallel cables. Other cable lengths are available on request. In addition to this pendant lamp with direct light output, one with additional uplight is also offered.

The Bullauge 6 can be regulated with a leading edge or trailing edge phase dimmer. DALI, Push or 1-10 Volt dimmable lamps are also available on request. In addition, other diameters up to 120 cm and other RAL colours are offered for the lamp on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.