



less'n'more

Athene Wall Light A-BWL2

Dimmbarkeit

- Variateur tactile sur le support mural
- dimmerable sur place avec commande gradateur de phase inverse


Oberfläche

- aluminium
- noir
- blanc

flexible_arm

- vert Textile
- rouge Textile
- marron Textile
- blanc Textile
- noir Textile
- bleu textile
- anthracite Textile
- aluminium

Technical details

Pays de fabrication	 Allemagne
fabricant	less'n'more
concepteur	less'n'more
protection	IP43
Contenu de la livraison	LED
matériel	aluminium, verre
angle du faisceau	25 - 100 degrees
Puissance en Watt	4,8 W
LED	y compris
Indice de rendu des couleurs	90
Flux lumineux en lm	600
La température de couleur en Kelvin	2.700 extra blanc chaud
tête de luminaire masse	7 cm
remplacement des ampoules :	sur le site meme
Support mural Dimensions	8 cm
Dimensions	H max. 63 cm

Description

The Less'n'more Athene Wall Light A-BWL2 is mounted on the wall as standard. It is also suitable for mounting on a flush-mounted box. Its mounting plate or wall bracket has a diameter of 8 cm and can be freely mounted 360 degrees during installation. This Athene wall lamp has a flexible lamp arm that can be stretched and bent as desired. With a maximum extension of the lamp arm, the lamp has a height of 63 cm. The flexible arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

The lamp head and wall bracket are offered in the surfaces aluminum and black. By turning the glass lens out of or into the lamp head, the beam angle of the light can be continuously adjusted between 25 and 100 degrees. With a larger beam angle, the light is distributed over a larger area. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as the light source.

The Athene Wall Light A-BWL2 is available on site dimmable with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in additional special colours on request. In addition, the lamp is also available on request with a supply cable and safety plug for direct connection to a power supply.