

# Betec


## Angulus 25 cm Typ 15



### Oberfläche

- chrome
- or mat
- Laiton brillant
- Laiton mat
- nickel brillant
- matte de nickel
- noir
- Browning
- or brillant

### Technical details

<b>Pays de fabrication</b>	 Allemagne
<b>Fabricant</b>	Betec
<b>Créateur</b>	Horst Lettenmayer
<b>Indice de protection / Indice IP</b>	IP20
<b>Contenu de la livraison</b>	LED
<b>Projection en cm</b>	15
<b>matériel</b>	laiton
<b>Puissance en Watt</b>	8 W
<b>LED</b>	y compris
<b>Indice de rendu des couleurs</b>	>90
<b>Flux lumineux en lm</b>	689,9
<b>La température de couleur en Kelvin</b>	2.700 extra blanc chaud
<b>Dimensions</b>	H 21,5 cm   L 25 cm

### Description

With its angular shape, the Betec Angulus fits particularly harmoniously with many picture frames. Its lamp head can be rotated around its own axis so that it can be realigned at any time if required. This makes this lamp particularly suitable for illuminating pictures, menus and music stands. A Duo LED is integrated as the light source. A Duo LED consists of two LEDs in one housing and therefore has a particularly high light output. The lamp is supplied with a diffuser cover that reduces the glare of the emitted light. Here, the Angulus is offered with a length of 25 cm and a projection of 15 cm (bracket type 15).

The Betec Angulus 25 cm is offered in the surfaces brass glossy, brass matt, chrome, nickel glossy, nickel matt, burnished, black matt, gold glossy and gold matt. The scope of delivery includes a mounting set with which the lamp can be easily attached directly to a picture or to the wall. The picture light has a colour temperature of 2,700 Kelvin extra warm white. On request, it is also available with 2,400 Kelvin extra warm white, 3,000 Kelvin warm white or 3,100 Kelvin white. The integrated LED is characterised by very good colour rendering with a high colour rendering index of Ra >90. A touch dimmer is offered as an accessory, with which the lamp can be switched and dimmed by touch. The manufacturer Betec offers the Angulus picture light also in three other lengths and with a projection of 20 cm or 25 cm.