

Mawa

Wittenberg 4.0 ceiling lamp headflush LED

Oberfläche

- noir
- blanc

Farbtemperatur in Kelvin

- 2.700 extra blanc chaud
- 3.000 blanc chaud
- 4.000 blanc

Technical details

Pays de fabrication

N/

fabricant

concepteur

.....

concepteur 2

année

protection

Contenu de la livraison

matériel

angle du faisceau

atténuation

Puissance en Watt

LED

Indice de rendu des couleurs

coulcuis

tête de luminaire masse

masse

remplacement des

ampoules:

Dimensions

Allemagne

Mawa

Jan Dinnebier

J.... -

mawa engineering

2021 IP20

LED

aluminium, métal

38 degres

gradable avec variateur à coupure de phase

et à commande de phase

12,7 W

y compris

95

8 cm

sur le site meme

H 10 cm | B 12 cm | L 12 cm

Description

The Mawa Wittenberg 4.0 ceiling lamp head-flush LED has an adjustable spotlight lamp head. This lamp head is integrated completely flush in the rectangular ceiling housing, i.e. it disappears completely into the ceiling housing when folded in. It can be rotated by 365 degrees and swivelled by 90 degrees. The large light-emitting surface of the spotlight head is well glare-reduced. The compact design of the lamp means that neither screws nor cables are visible. This ceiling lamp is available with a powder-coated matt white (RAL 9016) or matt black finish (RAL 9005).

The integrated LED is offered with a colour temperature of 2,700 Kelvin extra warm white, 3,000 Kelvin warm white or 4,000 Kelvin white. On request, it is also available with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,100 Kelvin warm white to 1,850 Kelvin extra warm white). The Wittenberg 4.0 ceiling light head-flush LED can be dimmed on site with a trailing edge or leading edge phase dimmer; on request, it is also available as a DALI dimmable version or a version that can be dimmed by smartphone via Bluetooth.

The spotlight has a beam angle of 38 degrees. The beam angle determines the angle at which the light emerges from an LED spotlight. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the Order comments field.