



Knapstein

HELLI-1

Oberfläche

- nickel
- noir
- bronze

Struktur

- Nickel
- noir
- bronze

Technical details

Pays de fabrication

Allemagne

fabriquant

Knapstein

année

2023

Diamètre en cm

8

matériel

Acryl, Metall

réglage de la hauteur

réglable en hauteur

atténuation

contrôle gestuel

Puissance en Watt

2x8 W

LED

inclus

Indice de rendu des couleurs

>90

Flux lumineux en lm

2140

La température de couleur en Kelvin

2.700 blanc chaud extra

protection

IP20

Contenu de la livraison

LED

baldaquin

Ø9cm

remplacement des ampoules :

chez le fabricant / a l'usine

hauteur totale

70 - 170 cm

Dimensions

Ø 8 cm

Description

The Knapstein Helli-1 LED pendant lamp has a cylindrical lamp body with freely combinable structures on the underside of the luminaire. The glass of the lower diffuser of the luminaire is reversible, making it easy to choose between a lens for a focussed lighting effect and a disc for a diffuse lighting effect. To do this, unscrew the lower light ring and place the enclosed glass in the desired position (lens/disc). The aforementioned screw ring (structure) is available in 3 different colours. A swiping hand movement in the sensor area switches the corresponding light source on or off. To dim the light, the hand is held in front of the respective sensor until the desired light intensity is reached. Thanks to the integrated memory function, the last settings are saved and are immediately available again the next time the light is switched on. The uplight and downlight can be switched and dimmed separately using gesture control. With the built-in lift height adjustment, the luminaire height can be continuously adjusted from approx. 70 cm - 170 cm. The Knapstein Helli-1 has a synchronisation function for adjusting the light intensity of all light sources on one side of the luminaire. The ceiling canopy of the Knapstein Helli-1 LED pendant lamp has a magnetic holder, so no external screw connections are visible. This pendant lamp is available in several surfaces and freely combinable external structures on the underside.