

Byok

Piani Mono 125 Downlight



Oberfläche

- Gepolijst aluminium
- mat aluminium
- matzwart

Leuchte

- hoogte verstelbaar
- hoogte verstelbaar

Technical details

| | |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|
| Land van herkomst |  Duitsland |
| Fabrikant | Byok |
| Ontwerper | Kai Byok |
| Beschermingsklasse / IP-bescherming | IP20 |
| Leveringsomvang | LED |
| materiaal | aluminium |
| kabellengte | 300 cm |
| dimmen | dimbaar op locatie met faseafsnijding dimmer |
| LED | inclusief |
| Kleurweergave-index | >90 |
| Kleurtemperatuur in Kelvin | 2.700 extra warm wit |
| bulb vervangen: | bij de fabrikant / fabriek |
| prestaties van het systeem | 8 x 3,6 Watt |
| Totale lichtstroom in lm | 2.440 |
| Dimensions | H 1 cm B 5 cm L 125 cm |

Omschrijving

The Byok Piani Mono 125 is a pendant lamp. It is part of the Piani collection designed by Byok. Its unusual shape is only 1 cm thin. This lamp pleasantly illuminates the room in an almost agravic way. The eight LED bulbs are placed inside sockets so that you may exchange them singly. Following surfaces are offered: aluminum matt, aluminum polished or black matt. The light is offered either height-determinable (can be set to the desired length during assembly) or height-adjustable (the overall height can also be adjusted after assembly).

The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.