

# Byok

## Piani Mono 165 Downlight



### Oberfläche

- Gepolijst aluminium
- mat aluminium
- matzwart

### Leuchte

- hoogte verstelbaar
- hoogte verstelbaar

## Technical details

<b>Land van herkomst</b>	 Duitsland
<b>Fabrikant</b>	Byok
<b>Ontwerper</b>	Kai Byok
<b>Beschermingsklasse / IP-bescherming</b>	IP20
<b>Leveringsomvang</b>	LED
<b>materiaal</b>	aluminium
<b>kabellengte</b>	300 cm
<b>dimmen</b>	dimbaar op locatie met faseafsnijding dimmer
<b>LED</b>	inclusief
<b>Kleurweergave-index</b>	>90
<b>Kleurtemperatuur in Kelvin</b>	2.700 extra warm wit
<b>bulb vervangen:</b>	bij de fabrikant / fabriek
<b>prestaties van het systeem</b>	10 x 3,6 Watt
<b>Totale lichtstroom in lm</b>	3.060
<b>Dimensions</b>	H 1 cm   B 5 cm   L 165 cm

## Omschrijving

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.