

Byok

Grado L


Oberfläche

- mat aluminium
- matzwart
- mat wit

Dimmbaarheid

- DALI dimbaar
- Daglicht en bewegingssensor met sensor voor Uplight

Technical details

| | |
|--|---|
| Land van herkomst |  Duitsland |
| Fabrikant | Byok |
| Ontwerper | Kai Byok |
| Beschermingsklasse / IP-bescherming | IP20 |
| Leveringsomvang | LED |
| Projectie in cm | 151 |
| materiaal | aluminium |
| kabellengte | 300 cm |
| Wattage | 87 W |
| Kleurweergave-index | 80 |
| Kleurtemperatuur in Kelvin | 3.000 warm wit |
| kandelaar Dimensions | 50 x 35 cm |
| Totale lichtstroom in lm | 14.000 |
| lichtverdeling | direct en indirect |
| Dimensions | H 204 cm |

Omschrijving

The Byok Grado L is a floor lamp with a 151 cm long arm. The lamp can be fixed directly to the furniture or be positioned movably with one base. It is particularly suitable for a single workstation. The Grado L 2 and T 4 from the series are also available for up to two or four workstations. The Grado L emits light simultaneously upwards and downwards. It is available in three versions: DALI dimmable or with an integrated daylight and motion sensor with an additional sensor for uplight. The surfaces available are matt anodised aluminum, matt white and matt black. As standard, this floor lamp is supplied with a colour temperature of 3,000 Kelvin warm white, on request it is also offered with 4,000 Kelvin white.