



Cini & Nils

Acqua with double canopy

Oberfläche

- goud
- zilver
- wit

Version

- Downlight
- Uplight

Technical details

Land van fabricage	 Italië
fabrikant	Cini & Nils
ontwerper	Luta Bettonica
jaar	2014
bescherming	IP20
Omvang van de levering	LED
materiaal	aluminium, staal
hoogteverstelling	hoogte bepaalbaar
dimmen	met schakelaargestuurde, geïntegreerde dimmer
LED	inclusief
Kleurweergave-index	95
Kleurtemperatuur in Kelvin	2.800 warm wit
luifel Dimensions	Lengte 33 cm, breedte 11 cm, hoogte 5 cm
prestaties van het systeem	5 x 5,6 Watt
Totale lichtstroom in lm	3.250
totale hoogte	200 cm
Dimensions	H 86 cm

Omschrijving

This Cini & Nils Acqua consists of two multiple lamps suspended next to each other on a canopy. A total of five lighting elements are integrated. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The oval canopy is supplied in the matching surface to the lamp. The Acqua is offered in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light directed downwards.

The pendant light with multiple canopy is operated with a switch-controlled, integrated dimmer, with which the light can be dimmed continuously via the normal light switch. No additional cables are required for this. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To set the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and automatically selected again when the light is switched on again. On request, the Acqua with double canopy is also available on site dimmable with Push.

This light has a total of five individual Acqua elements. On request, the pendant lamp is also available with up to ten elements. The pendant light has a maximum height of 200 cm, the cables can be shortened if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of the power supply.