



# SLV

## Ovalisk 100

### Version

- Pike Earth
- te schroeven
- voor in gegoten beton

## Technical details

|  |   |
|--|---|
| <b>Land van herkomst</b>                   |  Duitsland |
| <b>Fabrikant</b>                           | SLV   |
| <b>Beschermingsklasse / IP-bescherming</b> | IP65  |
| <b>Leveringsomvang</b>                     | LED   |
| <b>Diameter in cm</b>                      | 15  |
| <b>materiaal</b>                           | aluminium, glas   |
| <b>oppervlak</b>                           | antraciet   |
| <b>Wattage</b>                             | 9 W   |
| <b>LED</b>                                 | inclusief   |
| <b>Kleurweergave-index</b>                 | >80   |
| <b>Lichtstroom in lm</b>                   | 560 - 600   |
| <b>Kleurtemperatuur in Kelvin</b>          | 3.000 warm wit - 4.000 Kelvin wit   |
| <b>Diffuser diameter</b>                   | 17 cm   |
| <b>lichtverdeling</b>                      | licht in de kamer   |
| <b>totale hoogte</b>                       | 100 cm  |
| <b>Dimensions</b>                          | Ø 15 cm   |

## Omschrijving

The SLV Ovalisk 100 outdoor free-standing lamp can be fixed to the floor using three existing holes in the lower flange of the lamp. The lamp is also available with a concrete anchor for mounting on uncured concrete bases or mobile with a galvanised stainless steel ground spike for unpaved beds and green areas. This matt anthracite aluminium LED lamp has a diameter of 14.8 cm and is available in a height of 100 cm. If required, the colour temperature of the lamp can be changed from 3000 Kelvin warm white to 4000 Kelvin white using a switch (CCT Switch) integrated in the lamp. The glass diffuser has a diameter of 17 cm. With its IP65 protection rating, SLV's Ovalisk 100 is ideal as an outdoor lamp because it is dust-tight and protected against water jets from any angle. An IP68 junction box, required to connect the lamp, is also available as an accessory.