

# Mawa


## Bullaage 6 wall distance mounting

### Durchmesser in cm

- 45
- 60
- 80
- 120



### Technical details

<b>Kraj produkcji</b>	 Niemcy
<b>Producent</b>	Mawa
<b>Projektant</b>	Martin Wallroth
<b>powierzchnia</b>	weiß matt / white matt
<b>Stopień ochrony / Stopień ochrony IP</b>	IP20
<b>Zawartość opakowania</b>	LED
<b>tworzywo</b>	aluminium, szkło akrylowe
<b>ściemnianie</b>	ściemniające z przycinaniem fazy i ściemniaczem z regulacją fazy
<b>LED</b>	Łącznie
<b>dystrybucja światła</b>	bezpośrednio
<b>wysokość całkowita</b>	15 cm
<b>Dimensions</b>	H 10 cm

### Opis

The Mawa Bullaage 6 wall distance mounting is a wall or ceiling lamp. It has a distance of 5 cm to the wall or ceiling thanks to the supplied spacer. This gives it a total height of 15 cm in all sizes. On request, the lamp is also available with a different distance. The lamp is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, it has an aluminum housing in powder-coated white matt. Due to the even arrangement of the LEDs and the opaque, satinized diffuser made of plexiglass, the lamp has a diffuse and very homogeneous lighting surface. The wall and ceiling lamp can be easily installed with its patented closure.

The Bullaage 6 wall distance installation can be regulated with a leading edge or trailing edge phase dimmer. On request the light is also available DALI, 1-10 Volt or Push dimmable. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white. In addition, the wall and ceiling light is offered on request with a different diameter up to 120 cm, in other RAL colours or with upright. Furthermore the lamp is also available for direct wall or ceiling mounting.