




Knapstein

AURA-L

Oberfläche

- nikiel
- czarny

Technical details

Kraj produkcji	 Niemcy
Producent	Knapstein
Projektant	Knapstein
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
Projekcja w cm	50
tworzywo	aluminium, metal
ściemnianie	kontrola gestow
LED	łącznie
Wskaźnik oddawania barw	>90
Temperatura barwowa w stopniach Kelvina	2.700 extra biała ciepła
świeczniku Wymiary	28 cm
wydajność systemu	1 x 43 Watt + 1 x 10,8 Watt
Całkowity strumień świetlny w lm	6.300
Dimensions	H 184 cm

Opis

The Knapstein AURA-L emits its light upwards as a ceiling floodlight. The lamp has a rotating and swivelling reading arm. The lamp head on the reading arm can be swivelled independently of the reading arm. The Uplight of the ceiling floodlight and the light of the lamp head can be switched and dimmed separately by gesture control.

The sensor area for the ceiling floodlight is located in the centre of the light rod, for the reading arm in the lower area of the plexiglass cover at the bottom of the lamp head. The respective light source is switched on or off with a wiping hand movement in the sensor area. To dim the individual light source continuously, the hand is held at or below the sensor for a longer period of time. Using the memory function, the last set light intensity is saved and automatically selected the next time it is switched on. In the event of a mains failure, the light is automatically switched on if it was previously on. It remains switched off if it was also switched off prior to the power failure. This function is suitable for use with switchable sockets.

The AURA-L from Knapstein is available in black and matt nickel-plated surfaces. The floor lamp is also offered without reading arm.