



less'n'more

Athene Wall Light A-BWL2

Dimmbarkeit

- Ściemniacz dotykowy na uchwycie ściennym
- Ściemniacz kontroli faz przyśiemniania

Oberfläche

- aluminium
- czarny
- biały

flexible_arm

- antracyt Tekstylia
- aluminium
- zielona Tekstylia
- czerwony Tekstylia
- brązowy Tekstylia
- białe Tekstylia
- noir Tekstylia
- niebieski Tekstylia

Technical details

Kraj produkcji	Niemcy
producent	less'n'more
projektant	less'n'more
ochrona	IP43
zakres dostawy	LED
tworzywo	aluminium, szkło
kąt nachylenia belki	25 - 100 stopni
Moc w watach	4,8 W
LED	Łącznie
Wskaźnik oddawania barw	90
Strumień świetlny w lm	600
Temperatura barwowa w stopniach Kelvin	2.700 extra biała ciepła
Główica lampy Wymiary	7 cm
wymiana żarówek:	na miejscu
Uchwyt ścienny Wymiary	8 cm
Dimensions	H max. 63 cm

Opis

The Less'n'more Athene Wall Light A-BWL2 is mounted on the wall as standard. It is also suitable for mounting on a flush-mounted box. Its mounting plate or wall bracket has a diameter of 8 cm and can be freely mounted 360 degrees during installation. This Athene wall lamp has a flexible lamp arm that can be stretched and bent as desired. With a maximum extension of the lamp arm, the lamp has a height of 63 cm. The flexible arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

The lamp head and wall bracket are offered in the surfaces aluminum and black. By turning the glass lens out of or into the lamp head, the beam angle of the light can be continuously adjusted between 25 and 100 degrees. With a larger beam angle, the light is distributed over a larger area. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as the light source.

The Athene Wall Light A-BWL2 is available on site dimmable with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in additional special colours on request. In addition, the lamp is also available on request with a supply cable and safety plug for direct connection to a power supply.