

Mawa

Seventies mounted spotlight Downlight LED dimmable

Oberfläche

- czarny
- biały

Farbtemperatur in Kelvin

- 2.700 extra biała ciepła
- 3.000 biała ciepła

Technical details

Średnica w cm

Kraj produkcji
producent
Mawa
projektant
projektant 2
Jan Blieske
projektant 2
rok
2020
ochrona
IP20
zakres dostawy
Niemcy
Niemcy
Nawa
Autor
Nawa
Jan Blieske
Jan Dinnebier
LED

tworzywoaluminiumkąt nachylenia belki30 stopni

ściemnianie ściemnialna kontroli faz przyciemniania

9

Moc w watach25 WLEDŁącznieWskaźnik oddawania barw>90

Dimensions H 18 cm \mid Ø 9 cm

Opis

The Mawa Seventies mounted spotlight Downlight LED emits its light directly and bundled downwards. The ceiling light has a height of 18.4 cm and a diameter of 9 cm. Thanks to its compact design, there are no visible screws. The lamp is offered in the powder-coated surfaces white or black matt. On request, it is also available in other RAL colours.

The Seventies mounted spotlight Downlight LED is offered with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white. On request, it is also available with 4,000 Kelvin white. This light can be dimmed on site with a trailing edge phase dimmer. A DALI dimmable version is also available on request. The lamp's colour rendering index is Ra >90, but it is also available with Ra >95 on request, which is closer to natural light (Ra 100).

sciemnialna kontroli faz przyciemniania

The Seventies mounted spotlight Downlight LED has a beam angle of 30 degrees as standard. With a larger beam angle, the light is distributed over a larger area. Optionally, the cylindrical ceiling lamp can also be ordered with a beam angle of 16 or 22 degrees in the field Order Comment.