

Steng

Tolou Pendant Lamp



Schirmfarbe

- biały
- czarny


Dimmbarkeit

- DALI ściemniania
- ściemniające z przecinaniem fazy i ściemniaczem z regulacją fazy
- z modulem Casambi

Farbtemperatur in Kelvin

- 2.700 extra biała ciepła
- 3.000 biała ciepła

Technical details

Kraj produkcji	 Niemcy
producent	Steng
projektant	speziell
rok	2020
ochrona	IP20
zakres dostawy	LED
Średnica w cm	46
tworzywo	aluminium, tekstylny
długość kabla	200 cm
regulacja wysokości	wysokość ustalona
Moc w watach	29 W
LED	łącznie
Wskaźnik oddawania barw	>90
Strumień świetlny w lm	3.100
baldachim Wymiary	18 cm
Dimensions	H 7 cm Ø 46 cm

Opis

The Steng Tolou pendant lamp has a ring-shaped fabric lamp shade with an elegant filigree suspension. It emits light both upwards and downwards. The cable is directed to the side of the lamp shade via a deflector. It has a maximum length of 200 cm and can be shortened if necessary.

The Tolou is available in the shade colours black or white. The lamp shade is 7.1 cm high and has a diameter of 46 cm. As standard, the lamp is delivered with a cable diverter in chrome. The Tolou pendant lamp is operated with an integrated LED, which is offered with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white.

This lamp is available in three versions: on site dimmable with a trailing edge or leading edge phase dimmer, DALI dimmable or with a Casambi module.

In the version with a trailing edge or leading edge phase dimmer, the uplight and the downlight can be switched separately by the series switching module integrated in the lamp. Only one switch or dimmer on the wall is required for this.

The switching sequence is as follows:

- Switch On = Downlight on
- Switch On / Off / On = Uplight on
- Switch On / Off / On / Off / On = both on

With this version, uplight and downlight can only be dimmed together.

With the DALI dimmable version, uplight and downlight can be switched and dimmed separately.

With the version with a Casambi module, uplight and downlight can also be switched and dimmed separately. The uplight and downlight are then controlled and dimmed via the free Casambi app via Bluetooth using a smartphone or tablet.

Another version is also available on request. This optional version can be dimmed on site with a trailing edge or leading edge phase dimmer. With this

version, the uplight and downlight can only be switched separately if a 4-wire mains cable is available on site. This means that the uplight and downlight can be switched with 2 different switches. If only a normal 3-wire mains cable is available, the lamp can still be dimmed, but the uplight and downlight can only be switched together.

On request, the pendant lamp is also available in other shade colours and in other diameters. The cable diverter is also offered in gold or black on request. On request, the lamp by Steng is also available with a colour temperature of 4,000 Kelvin white.